



REV	ECN NO.	DATE
G	工程變更	
H		2005.06.16

Material:
 Insulator: PBT+30% Glass Fiber (UL94V-0).
 Contact: Copper Alloy with Gold or Tin over Nickel Plated.
 Specification:
 Current Rating: 1 Amp.
 Withstanding Voltage: AC 500V for 1 Minute.
 Insulation Resistance: 1000M Min. at DC 500V.
 Contact Resistance : 15m Max.,
 Operating Temperature: -40°C ~ +105°C.

Pos.	Dim. A	Dim. B	Dim. C	Pos.	Dim. A	Dim. B	Dim. C
6	11.20	5.00	4.00	34	39.20	33.00	32.00
8	13.20	7.00	6.00	36	41.20	35.00	34.00
10	15.20	9.00	8.00	38	43.20	37.00	36.00
12	17.20	11.00	10.00	40	45.20	39.00	38.00
14	19.20	13.00	12.00	44	49.20	43.00	42.00
16	21.20	15.00	14.00	48	53.20	47.00	46.00
18	23.20	17.00	16.00	50	55.20	49.00	48.00
20	25.20	19.00	18.00	54	59.20	53.00	52.00
22	27.20	21.00	20.00	56	61.20	55.00	54.00
24	29.20	23.00	22.00	60	65.20	59.00	58.00
26	31.20	25.00	24.00	62	67.20	61.00	60.00
28	33.20	27.00	26.00	64	69.20	63.00	62.00
30	35.20	29.00	28.00	68	73.20	67.00	66.00
32	37.20	31.00	30.00	80	85.20	79.00	78.00

	SIGNATURE	DATE	TITLE: 2.0mm IDC Connector With Nose Type		CODE NO.	PBT	TOLERANCE:
1	DRN.	2005.06.16			CUS. NO.		XX.
	CHK.		J&W. P/N:	CUS. P/N:	SCALE	1:1	X. ± 0.2
	APP.		成品圖		UNIT	mm	.X ± 0.10
					PAGE	1/1	.XX ± 0.05
							ANG.

Chang Enn Co., Ltd.

DRAWING NO.	
PNH33	