


1		2		3		4		5		6		7		8	
REV.	ECN NO	LOCATIONS		DESCRIPTION				DATE	REVISER	APPD					



Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.30mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total mating force: 4.0 Kgf Max.
- 2.6 Total unmating force: 0.5 Kgf Min.
- 2.7 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10U",15u",30u".

3	Hood	1	P.B.T	UL 94-V0	Black
2	Contact	7	Brass	T=0.30mm	Gold Flashed
1	Housing	1	P.B.T or L.C.P	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO:		MATERIAL:		CHANG ENN CO., LTD.	
MODEL NO:		FINISH:			
UNIT: mm	SIZE: A4	COLOR:		PART NAME:	
TOLERANCE UNSPECIFIED		DR: '06/03/03		SERIAL ATA 7PIN(F)加後塞	
.x ±0.3	.xx ±0.20	CHK: '06/03/03		DWG NO: PND31-02	
.xxx ±0.100	ANG. ±1°	APP: '06/03/03		REV: AO	
SCALE: 4:1				SHEET: 1 of 1	