



REV.	ECNNO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Note:

1. Material:
  - 1.1 Insulator: PA66 UL 94-V0 rated.
  - 1.2 Contact: Brass, t=0.30mm.
2. Specification:
  - 2.1 Current rating: 1.0 A Max.
  - 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
  - 2.3 Contact resistance: 30 mΩ Max.
  - 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
  - 2.5 Total mating force: 4.0 Kgf Max.
  - 2.6 Total unmating force: 1.0 Kgf Min.
  - 2.7 Temperature range: -55°C~+85°C

3. Finishes:

- 3.1 Contacts: Gold flashed 1u", 3u", 5u", 10u", 15u", 30u".

NO.	NAME	Q'TY	MATERIAL	REMARKS&THICKNESS	FINISH
2	CONTACT	15	BRASS	T=0.3MM	GOLDFLASHED
1	HOUSING	1	PA66	UL94-V0	BLACK

PRATNO:	MATERIAL:	CHANG ENN CO., LTD.			
MODELNO:	FINSH:				
UNIT: MM	SIZE: A4	COLOR:	PARTNAME:		
TOLERANCE UNSPECIFIED		DR: '06/10/04	SERIAL ATA-15PIN(F) 焊線式 選擇		
.X-----±0.30		CHK: '06/10/04	DWGNO: PND31-05	REV. AD	
.XX-----±0.20		APP: '06/10/04	SCALE: 3:1	SHEET: 10F1	
.XXX-----±0.10					
ANG.-----±1°					