



**Material:**

1. Insulator: PBT Glass Fiber UL94-V0.
  2. Contact: Brass.
  3. Contact Plated: Gold-Plated Over Nickel.
- Specification:**
1. Current Rating: 1A AC,DC.
  2. Voltage Rating: 250V AC,DC.
  3. Contact Resistance: 20mΩ Min.
  4. Operating Temperature: -40°C to +105°C.
  5. Insulation Resistance: 1000MΩ Min.
  6. Withstanding Voltage: 500V AC/Min.

No. of Contacts	Dim. A	Dim. B
6P	12.32	5.08
8P	14.86	7.62
10P	17.40	10.16
12P	19.94	12.70
14P	22.48	15.24
16P	25.02	17.78
18P	27.56	20.32
20P	30.10	22.86
22P	32.64	25.40
24P	35.18	27.94
26P	37.72	30.48
28P	40.26	33.02
30P	42.80	35.56
34P	47.88	40.64
40P	55.50	48.26
44P	60.58	53.34
50P	68.20	60.96
60P	80.90	73.66
64P	85.98	78.74



長榮有限公司  
Chang Enn Co., Ltd.

NO.410, FU-TEH 1ST ROAD,  
SHIJR, TAIPEI COUNTY  
221, TAIWAN, R.O.C.

TEL: 886-2-26945824

FAX: 886-2-26946971

TITLE

PARTS NO.

DWG, NO.

2.54\*2.54  
IDC Socket Connector  
and S.R.

PNH43

GENERAL  
TOLERANCE

DIM:  
X. ±0.30  
X.X ±0.20  
X.XX±0.10

DRAWN

CHECK

APPROVE

SCALE

DATE

DATE

REV.

UNIT

93/12/01

103/11/13

C-BSC47

MM